

Performance

Tipping load (ISO 14397-1)	1215 kg
Rated operating capacity (ISO 14397-1)	608 kg
Pump capacity	64.00 L/min
System relief at quick couplers	22.4-23.1 MPa
Max. travel speed (high range - option)	14.8 km/h

Engine

Make / Model	Kubota / V2403-MDI-E3
Fuel	Diesel
Cooling	Liquid
Power at 2700 RPM	35.9 kW
Torque at 1600 RPM (SAE J1995 Gross):	158.6 Nm
Number of cylinders	4
Displacement	2433 cm ³
Fuel tank	54.50 L

Weights

Operating weight	2365 kg
Shipping weight	2052 kg

Controls

Vehicle steering	Direction and speed controlled by two hand levers
Loader hydraulics tilt and lift	Separate foot pedals or Joystick Controls (JC)
Front auxiliary (standard)	Electrical switch on right-hand steering lever

Drive System

Transmission	Infinitely variable tandem hydrostatic piston pumps, driving two fully reversing hydrostatic motors
--------------	---


Standard Features

Standard Seat	Electrically activated proportional front auxiliary hydraulics
Standard Cab with rear window ¹	Engine/hydraulics system shutdown
Seat belt	Manual
Seat bar	Lift arm support
Automatically activated glow plugs	Operating lights, front and rear
Auxiliary hydraulics: variable flow/maximum flow	Parking brake
Bob-Tach™ frame	Horn
Bobcat Interlock Control System (BICS)	Spark arrestor muffler
10 x 16.5, 10-ply, Heavy duty tyres	Warranty: 24 months or 2000 hours (whichever occurs first)

1. Roll Over Protective Structure (ROPS) – meets requirements of SAE-J1040 and ISO 3471; Falling Object Protective Structure (FOPS) - meets requirements of SAE-J1043 and ISO 3449, Level I

Options

Joystick controls with 2 speed	Strobe
Deluxe pressurized cab with heating	Beacon
Deluxe pressurized cab with HVAC	Back-up alarm
Hydraulic bucket positioning (including ON/OFF switch)	Noise reduction kit
10 x 16.5, 10-ply, Severe duty tyres	EAC certification
10 x 16.5, 10-ply, Versatile duty tyres	

Dimensions


(A) 3558.0 mm	(J) 2781.0 mm
(B) 1976.0 mm	(K) 587.0 mm
(C) 23.0°	(L) 40.0°
(D) 214.0 mm	(M) 91.0°
(E) 900.0 mm	(N) 1575.0 mm
(F) 2502.0 mm	(O) 1940.6 mm
(G) 3172.0 mm	(P) 1221.7 mm
(H) 26.0°	(Q) 1490.0 mm
(I) 2157.0 mm	(Q) 1355.0 mm

Attachments

Auger Accessories	Pallet Fork Accessories
Augers	Pallet Forks, Hydraulic
Backhoes	Planer Accessories
Bale Forks	Rear Stabilizers
Breaker Accessories	Root Grapples
Breakers	Scarifiers
Brushcat™ Rotary Cutters	Scrapers
Brush Saws	Seeders
Combination Buckets	Skeleton Buckets
Concrete Mixers	Snow Blades
Construction / Industrial Buckets	Snow Pushers
Diggers	Snow V-Blades
Dozer Blades	Sod Layers
Dumping Hoppers	Soil Conditioners
Flail Cutters	Spreader
Graders	Spreaders
Grapples, Industrial	Sweepers
Landplanes	Tillers
Landscape Rakes	Tilt-Tatch
Laser Equipment	Utility Forks
Low Profile Buckets	Utility Frames
Miscellaneous	Vibratory Rollers
Mowers	Wood Chippers